

An Overseas Associate Member of Lifting Equipment Engineers Association
UK & ISO 9001 Company

Grade 80 CHAIN SLING CHART (BS EN 818 - 4)

Chain Size	Single Leg	Two Leg Angle from leg to vertical		Three/ Four Leg Angle from leg to vertical	
	90°	0. To 45°	45° To 60°	0. To 45°	45° To 60°
8mm	2.00	2.80	2.00	4.25	3.00
10mm	3.15	4.25	3.15	6.70	4.74
13mm	5.30	7.50	5.30	11.20	8.00
16mm	8.00	11.20	8.00	17.00	11.80
18 mm	10.00	14.00	10.00	21.25	14.75
20mm	12.50	17.50	12.50	26.50	19.00
22mm	15.00	21.20	15.00	31.50	22.40
26mm	21.20	30.00	21.20	45.00	31.50
32mm	31.50	45.00	31.50	67.00	47.50

Working Load Limit In Tonnes

* All slings are provided with Anodised Aluminium Tag and Test Certificates


CHAIN SLING COMBINATIONS




Endless



Single Leg



Two Leg
(With Grab Hook)



Three Leg



Four Leg
(With Shortening Clutch)

CHAIN SLING ACCESSORIES



Masterlink For
1 & 2 Leg



Masterlink For
Assly For 3/4 Leg



Connecting Link



Shortening
Clutch



Clevis Grab
Hook



Clevis Hook
With Latch



Clevis Self-
Locking Hook



Swivel Self
Lock Hook



Ratchet
Load Binder



Lever
Load Binder