

# Electric Wire Rope Hoist

Technical Data	MT500		MT1000	
	Standard Version	Version with double load cap.	Standard Version	Version with double load cap.
Load Capacity	250 kg	500 kg	500 kg	1000 kg
Lifting Height	12 m	6 m	20 m	10 m
Lifting Speed	10m/min	5m/min	8m/min	4m/min
Cable length	12 m		20 m	
Cable diameter	4.5 mm		6.0 mm	
Resister Cable	≥1600kg		≥3000kg	
Service	S3 20% - 10 min		S3 20% - 10 min	
Mains Voltage	230V~50Hz		230V~50Hz	
Motor performance	P1 1200 w		P1 1800 w	



# Electric Wire Rope Hoist with Trolley

Technical Data	MTWT-1000
Lift Weight (kg)	500/1000
Lift height (m)	20/10
Lift Speed (m/min)	8/4
Hoist Power (W)	1800
Trolley Power (W)	540
Power Supply	230V/50Hz
Trolley Speed m/min	13
Least Radii (m)	1.5
Recommend l steel Width (mm)	80-102
Wire rope dia (mm)	6.0
Weight of machine	54



**SAFE LIFT**<sup>®</sup>

**ELECTRIC WIRE ROPE HOIST**

Main Performance and Technical Specifications

**MICRO ELECTRIC  
ROPE HOIST  
500KG / 1000KG**



Model: SL-1000			
Load Capacity	500/1000kg	Lifting Speed	510m/min
Voltage	220V~50Hz	Rating Current	10A
Insulating Grade	B	Work Level	M 1
Protecting Grade	IP54	Input Power	2000W
Capacitance	70VF/450V	Work rate	S3-20% 10min
Wire Rope	Ø6.0mm	Machine NW	30.65kg
Lifting Height	20/10m		