

# SAFE LIFT<sup>®</sup>

## PLAIN & GEARED TROLLEY

Cap. tons	Fits/Beams mm				Dimensions mm								Minimum Revolving Radius mm	Wt. kgs	Type No.
	W		H		a	b	c	d	e	f	k				
	Min.	Max.	Min.	Max.											
<b>PLAIN TROLLEYS</b>															
$\frac{1}{2}$	75	125	100	150	206	174	120	45	55	27	—	900	6.0	AP-05	
1	75	125	125	250	206	231	120	45	80	27	—	1300	10.0	AP-10	
2	100	150	150	400	241	271	155	60	100	33	—	1500	18.5	AP-20	
3	100	150	180	400	261	311	185	70	113	47	—	2000	26.0	AP-30	
5	125	175	250	450	294	351	220	80	125	53	—	2600	44.0	AP-50	
10	150	175	250	450	294	721	165	—	125	53	—	—	96.0	AP-90	
<b>GEARED TROLLEYS</b>															
1	75	125	125	250	206	231	120	45	80	27	117	1300	14.0	AG-10	
2	100	150	150	400	241	271	155	60	100	33	119	1500	23.5	AG-20	
3	100	150	180	400	261	311	185	70	113	47	134	2000	33.5	AG-30	
5	125	175	250	450	294	351	220	80	125	53	134	2600	53.5	AG-50	
10	150	175	250	450	294	721	165	—	125	53	134	—	101.0	AG-90	

