

Polyester Webbing Sling

CITEX Polyester Webbing Sling are made of strong polyester adhere to 7:1 safety factor and is manufactured according to BS 3481 part 2 and it fulfils the S.W.L. (Safe Working Load) as stated on the label, which is attached to every sling



Technical Specification			FLAT POLYESTER WEBBING SLINGS SINGLE PLY STANDARD : BS: 3481 PART 2 SAFETY FACTOR : 7:1					
KGS	COLOUR	WIDTH	LOAD CAPACITIES IN KGS			LIFTING AN ANGLE		
			100%	200%	80%	7" - 45"	45 - 60"	
500	VIOLET	1 inch	500	1000	400	700	500	
1000	GREEN	2 inch	1000	2000	800	1400	1000	
1500	YELLOW	3 inch	1500	3000	1200	2100	1500	
2000	GREY	4 inch	2000	4000	1600	2800	2000	
2500	RED	5 inch	2500	5000	2000	3500	2500	
3000	BROWN	6 inch	3000	6000	2400	4200	3000	
4000	BLUE	8 inch	4000	8000	3200	5600	4000	
5000	ORANGE	10 inch	5000	10,000	4000	7000	5000	
6000	ORANGE	12 inch	6000	12,000	4800	8400	6000	

Technical Specification			FLAT POLYESTER WEBBING SLINGS DOUBLE PLY STANDARD : BS: 3481 PART 2 SAFETY FACTOR : 7:1					
KGS	COLOUR	WIDTH	LOAD CAPACITIES IN KGS			LIFTING AN ANGLE		
			100%	200%	80%	7" - 45"	45 - 60"	
1000	VIOLET	1 inch	1000	2000	800	1400	1000	
2000	GREEN	2 inch	2000	4000	1600	2400	2000	
3000	YELLOW	3 inch	3000	6000	2400	4200	3000	
4000	GREY	4 inch	4000	8000	3200	5600	4000	
5000	RED	5 inch	5000	10,000	4000	7000	5000	
6000	BROWN	6 inch	6000	12,000	4800	8400	6000	
8000	BLUE	8 inch	8000	16,000	6400	11,200	8000	
10,000	ORANGE	10 inch	10,000	20,000	8000	14,000	10,000	
12,000	ORANGE	12 inch	12,000	24,000	9600	16,800	12,000	

Technical Specification			FLAT POLYESTER WEBBING SLINGS 3 PLY STANDARD : BS: 3481 PART 2 SAFETY FACTOR : 7:1					
KGS	COLOUR	WIDTH	LOAD CAPACITIES IN KGS			LIFTING AN ANGLE		
			100%	200%	80%	7" - 45"	45 - 60"	
1500	VIOLET	1 inch	1500	3000	1200	2100	1500	
3000	GREEN	2 inch	3000	6000	2400	4200	3000	
4500	YELLOW	3 inch	4500	9000	3600	6300	4500	
6000	GREY	4 inch	6000	12,000	4800	8400	6000	
7500	RED	5 inch	7500	15,000	6000	10,500	7500	
9000	BROWN	6 inch	9000	18,000	7200	12,600	9000	
12,000	BLUE	8 inch	12,000	24,000	9600	16,800	12,000	
15,000	ORANGE	10 inch	15,000	30,000	12000	21,000	15,000	
18,000	ORANGE	12 inch	18,000	36,000	14400	25,200	18,000	

Technical Specification			FLAT POLYESTER WEBBING SLINGS 4 PLY STANDARD : BS: 3481 PART 2 SAFETY FACTOR : 7:1					
KGS	COLOUR	WIDTH	LOAD CAPACITIES IN KGS			LIFTING AN ANGLE		
			100%	200%	80%	7" - 45"	45 - 60"	
2000	VIOLET	1 inch	2000	4000	1600	2,800	2000	
4000	GREEN	2 inch	4000	8000	3200	5,600	4000	
6000	YELLOW	3 inch	6000	12,000	4800	8,400	6000	
8000	GREY	4 inch	8000	16,000	6400	11,200	8000	
10,000	RED	5 inch	10,000	20,000	8000	14,000	10,000	
12,000	BROWN	6 inch	12,000	24,000	9,600	16,800	12,000	
16,000	BLUE	8 inch	16,000	32,000	12,800	22,400	16,000	
20,000	ORANGE	10 inch	20,000	40,000	16,000	28,000	20,000	
24,000	ORANGE	12 inch	24,000	48,000	19,200	33,600	24,000	

ROUND SLING

- Protected with strong fabric;
- Available single cover and double cover;
- Manufactured according to EN 1492-2;
- With CE & GS Certificate issued by TUV.
- Safety Factor 7:1;
- Material 100% polyester;

