

Accord to SFS/EN-818
Safety Factor: 4:1

Rigging Hardware



Specification
6-8
7/8-8
10-8
13-8
16-8
20-8
22-8
26-8
32-8

Eye Grab Hook



Specification
6-8
7/8-8
10-8
13-8
16-8

Clevis shortening grab hook



Specification
6-8
7/8-8
10-8
13-8
16-8
20-8

Eye Sling Hook with Latch



Specification
6-8
7/8-8
10-8
13-8
16-8
20-8

Clevis Sling Hook with Latch



Specification
6-8
7/8-8
10-8
13-8
16-8

Eye Foundry Hook



Specification
6-8
7/8-8
10-8
13-8
16-8
20-8

Eye Swivel Hook with Latch



Specification
6-8
7/8-8
10-8
13-8
16-8
20-8
22-8
26-8

Eye Self-Locking Hook



Specification
6-8
7/8-8
10-8
13-8
16-8
20-8

Clevis Self-Locking Hook



Specification
1-T
3T
5T
8T

Weld On Hook



Specification
6-8
7/8-8
10-8
13-8

Clevis Shortening Clutch



Specification
M6
M8
M10
M12
M16
M20
M24
M30
M36
M42

Eye Bolt



Specification
M6
M8
M10
M12
M16
M20
M24
M30
M36
M42

Eye Nut



Specification
6-8
7/8-8
10-8
13-8
16-8
20-8
22-8

Weld Master Link



Specification
6-8
7/8-8
10-8
13-8
16-8
20-8

Welded Master Link Assembly



Specification
6-8
7/8-8
10-8
13-8
16-8
20-8
22-8

Welded Master Link With Flat



Specification
6-8
7/8-8
10-8
13-8
16-8
20-8

Welded Master Link Assembly With Flat



Specification
6-8
7/8-8
10-8
13-8
16-8
20-8
22-8

Connecting Link



Specification
6-8
7/8-8
10-8
13-8
16-8

Web Sling Connector



Specification
6-8
7/8-8
10-8
13-8

Omega Link



Lift Ring